

2004



# Express Passenger

## New For 2004

- Front passenger assist handle standard

## Models

G1500 Regular Wheelbase RWD	.....(CG13406)
G1500 Regular Wheelbase AWD	.....(CH13406)
G2500 Regular Wheelbase RWD	.....(CG23406)
G3500 Regular Wheelbase RWD	.....(CG33406)
G3500 Extended Wheelbase RWD	.....(CG33706)

## Powertrain

### Engine

#### Standard (1500)

Vortec 4300 V6 MFI	
HP (hp @ rpm)	.....200 @ 4400
Torque (lb-ft @ rpm)	.....250 @ 2800

#### Available (1500)

Vortec 5300 V8 SFI	
HP (hp @ rpm)	.....285 @ 5200
Torque (lb-ft @ rpm)	.....325 @ 4000

#### Standard (2500 and 3500)

Vortec 6000 V8 SFI	
HP (hp @ rpm)	.....300 @ 4400
Torque (lb-ft @ rpm)	.....360 @ 4000

### Transmission

#### Standard (1500)

4-speed automatic, electronically controlled with overdrive, tow/haul mode and internal transmission oil cooler

#### Standard (2500 and 3500)

4-speed automatic, heavy-duty, electronically controlled with overdrive, tow/haul mode and external transmission oil cooler

## Fuel Economy [Est. EPA<sup>1</sup> MPG (city/hwy)]

4.3L 1500 and 2500 <sup>1</sup>	.....15/20
5.3L 1500 and 2500 RWD <sup>1</sup>	.....14/18
AWD	.....14/18
6.0L 2500 and 3500	.....N/A

<sup>1</sup> 2003 Information

<sup>1</sup> Based on GM testing. Official EPA estimates not yet available.



## Select Mechanical Features

S = Standard, A = Available

	Base	LS
<b>Alternator</b> , 105 amps	S	-
<b>Alternator</b> , 145 amps	A	A
<b>Alternative fuel conversion-ready engine</b> , includes internal modifications for operation with natural or propane gas	A	A
<b>Battery</b> , 600 cold-cranking amps, includes rundown protection and retained accessory power	S	S
<b>Battery</b> , heavy-duty, 800 cold-cranking amps, includes rundown protection and retained accessory power	A	A
<b>Brakes</b> , 4-wheel antilock, 4-wheel disc	S	S
<b>Brake/transmission shift interlock</b> , automatic transmission	S	S
<b>Differential</b> , locking, heavy-duty, rear	A	A
<b>Exhaust</b> , aluminized stainless-steel muffler and tailpipe	S	S
<b>Frame</b> , ladder-type	S	S
<b>Oil life monitor</b>	S	S
<b>Suspension</b> , front, independent coil springs, and stabilizer bar (Requires rear-wheel drive Models)	S	S
<b>Suspension</b> , front, independent torsion bar (computer selected) and stabilizer bar (Requires all-wheel drive Models)	S	S
<b>Suspension</b> , rear, hypoid drive axle with multi-leaf springs	S	S
<b>Trailer equipment<sup>2</sup></b> , heavy-duty, includes trailering hitch platform and 7-lead wiring harness	A	A
<b>Trailer wiring</b> , 7-lead harness	A	A

## Select Exterior Features

	Base	LS
<b>Bumper</b> , front, painted Black	S	-
<b>Bumper</b> , front, chrome	-	S
<b>Bumper</b> , rear, painted Black step, includes pad	S	-
<b>Bumper</b> , rear, chrome step, includes pad	-	S
<b>Door</b> , swing-out passenger side, 60/40 split	S	S
<b>Door</b> , swing-out driver side, 60/40 split	A	A
<b>Door</b> , sliding passenger side	A	A
<b>Door beams</b> , steel-side	S	S
<b>Glass</b> , Solar-Ray light tinted, all windows	S	S
<b>Glass</b> , rear side door and rear door window, swing-out	S	S
<b>Glass</b> , Solar-Ray deep tinted (all windows except light tinted glass on windshield, driver and front passenger)	A	A
<b>Headlamps</b> , single rectangular halogen	S	-
<b>Headlamps</b> , dual composite halogen	-	S
<b>Mirrors</b> , outside rearview, manual folding, Black	S	S
<b>Mirrors</b> , outside rearview, manual folding, power adjust, heated, Black	A	A
<b>Mirrors</b> , outside rearview, manual folding, power adjust, heated, Black, includes turn signal indicators	A	A
<b>Tires</b> , front and rear, P235/75R16, all-season, blackwall (Requires 1500 Models)	S	S
<b>Tire</b> , spare P235/75R16, all-season, blackwall, located at rear underbody of vehicle (Requires 1500 Models)	S	S
<b>Tires</b> , front and rear, P235/75R16, all-season, white outlined-letter (Requires 1500 Models)	A	A
<b>Tire</b> , spare P235/75R16, all-season, white outlined-letter, located at rear underbody of vehicle (Requires 1500 Models)	A	A
<b>Tires</b> , front and rear, LT225/75R16E, all-season, blackwall (Requires 2500 Models)	S	S
<b>Tire</b> , spare LT225/75R16E, all-season, blackwall, located at rear underbody of vehicle (Requires 2500 Models)	S	S
<b>Tires</b> , front and rear, LT245/75R16E, all-season, blackwall (Requires 3500 Models)	S	S
<b>Tire</b> , spare LT245/75R16E, all-season, blackwall, located at rear underbody of vehicle (Requires 3500 Models)	S	S
<b>Trim</b> , rear body-colored halo (replaces standard black panels located above rear tail lamps)	A	A
<b>Wheels</b> , Gray painted, includes Gray center caps and steel spare	S	-
<b>Wheels</b> , Gray painted, includes chrome center caps and steel spare	A	S
<b>Wheels</b> , 4 - chrome-styled steel, includes Chrome center caps and steel spare (Requires 1500 Models)	A	A
<b>Wheels</b> , 4 - 16" x 7" cast aluminum, includes steel spare (Requires 1500 Models)	-	A
<b>Wipers</b> , intermittent, front wet-arm with pulse washers	S	S

## Available Exterior Colors\*

Berry Red Metallic

Black

Dark Gray Metallic

Dark Green Metallic

Indigo Blue Metallic

Light Pewter Metallic

Sandalwood Metallic

Summit White

Victory Red

**GM Fleet and Commercial**  
Because there's no other business like yours.™

www.gmfleet.com • 1-800-FLEETOPS

<sup>2</sup> Maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your Chevrolet dealer for additional details.

Information not to be reproduced for any use without permission of GM Fleet and Commercial. Please refer to the GM Online Guide for complete and updated ordering information.

\* Colors may not be available on all models. Actual colors may vary.

# Chevrolet Express Passenger

## Dimensions (in.)

	RWB	LWB
Wheelbase	135.0	155.0
Overall length	224.1	244.1
Body width	79.4	79.4
Overall height	81.6	82.0
Head room, 1st/2nd/3rd/4th/5th row*	40.2/38.5/38.6/38.1/38.1	
Shoulder room, 1st/2nd/3rd/4th/5th row*	68.8/68.9/63.5/68.3//62.7	
Hip room, 1st/2nd/3rd/4th/5th row*	65.5/66.0/64.4/59.6/63.2	
Leg room, 1st/2nd/3rd/4th/5th row*	41.3/34.8/37.6/39.8/36.4	
Step up height,		
front door 1500/2500+	17.9/19.4	19.3
side door 1500/2500+	18.8/20.2	20.0
Ground to top of rear load		
floor 1500/2500+	25.0/27.7	27.3
Cargo area height	51.9	51.9
Ground clearance, front	8.0/8.2	8.1
rear 1500/2500+	7.4/7.1	7.7

\* 4th row/5th row not available in 1500 Models and 5th row not available in 3500 RWB Model

+ Includes 2500 and 3500 Models

Published dimensions indicated are without optional equipment or accessories. Additional accessories or equipment ordered at the customer's request can result in a minor change in these dimensions.

## Standard Safety Features

- Adjustable front shoulder belt guides
- Adjustable rear shoulder belt guides (outboard)
- Air bag<sup>1</sup>, dual level driver and front passenger
- Antilock brakes, front and rear
- Automatic daytime running lamps
- Battery, maintenance free<sup>2</sup>
- Brake transmission shift interlock
- Child security rear door locks
- Disc brakes, front and rear with audible wear indicator
- Halogen headlamps
- L.A.T.C.H. system for compatible child restraints
- Laser etched VIN plate
- PASSLock theft deterrent
- Remote hood release
- Safety belt cinch capability for child seats
- Side window defogger, front
- Tinted glass windshield
- Tires with built-in tread wear indicators



## Select Interior Features

S = Standard, A = Available

	Base	LS
<b>Air bags<sup>1</sup></b> , frontal, driver and right front passenger (Includes passenger side air bag deactivation switch for models with 8600 lbs. GVWR and above)	S	S
<b>Air conditioning</b> , front manual	S	S
<b>Air conditioning</b> , rear	A	S
<b>Assist handle</b> , front passenger	S	S
<b>Child seat anchor</b> , located on all rear 3-passenger bench seating positions	S	S
<b>Console</b> , deluxe, includes glove box	-	S
<b>Cupholders</b> , 3, on engine console cover	S	S
<b>Defogger</b> , side window	S	S
<b>Defogger</b> , rear-window, electric	A	A
<b>Door locks</b> , power, includes Lock-out Protection	A	S
<b>Floor covering</b> , Black rubberized vinyl full length floor covering	S	-
<b>Floor covering</b> , color-keyed carpeting, includes front and rear rubberized vinyl floor mats	A	S
<b>Headliner</b> , cloth	S	S
<b>Heater</b> , rear, auxiliary	A	S
<b>Instrumentation</b> , analog, includes speedometer, odometer with trip odometer, fuel level, voltmeter, engine temperature and oil pressure	S	S
<b>Keyless entry</b> , remote, includes 2 transmitters and remote panic button	-	S
<b>Lighting</b> , 2 dome lamps, includes defeat switch and door handle-activated switches	S	S
<b>Lighting</b> , auxiliary, includes reading and underhood lights	A	S
<b>Mirror</b> , inside rearview, manual day/night	S	S
<b>Mirror</b> , inside rearview, electrochromic (light-sensitive auto dimming), 8-point compass and outside temperature indicator	-	A
<b>OnStar<sup>3</sup></b> – 1 Year Safe and Sound <sup>SM</sup> Plan included	A	A
<b>Power outlet</b> , auxiliary, 2 covered, on engine console cover, 12-volt	S	S
<b>Seat adjuster</b> , power, driver 6-way (riser only)	-	A
<b>Seat adjuster</b> , power, front passenger 6-way (riser only)	-	A
<b>Seats</b> , front vinyl reclining buckets, includes head restraints	S	-
<b>Seats</b> , front Custom Cloth buckets, includes head restraints and inboard armrests	A	S
<b>Seating</b> , 8-passenger (Standard on 1500)	S	S
<b>Seating</b> , 12-passenger (Standard on 2500, 3500)	S	S
<b>Seating</b> , 15-passenger (Available on 3500)	A	A
<b>Sound system</b> , ETR AM/FM stereo	S	S
<b>Sound system</b> , ETR AM/FM stereo with CD player	A	A
<b>Sound system</b> , ETR AM/FM stereo with CD and cassette player	A	A
<b>Sound system</b> , ETR AM/FM stereo with 6-disc CD changer	A	A
<b>Steering wheel</b> , steel sleeve column, includes theft-deterrent locking feature, Black	S	S
<b>Theft-deterrent system</b> , PASSLock	S	S
<b>Tow/haul mode selector</b> , IP mounted	S	S
<b>Visors</b> , padded, driver and passenger side with vinyl trim	S	S
<b>Visors</b> , padded, driver and passenger side with cloth trim and dual vanity mirrors, illuminated on passenger side	A	S

## Capacities

	1500 CG13406	1500 CH13406	2500 CG33406	3500 CG33406	3500 CG33706
<b>Curb weight</b> , lbs.	5245	5556	5864	6001	6321
<b>Max. cargo volume</b> , regular, with seats, cu. ft.	204	204	204	204	-
<b>Max. cargo volume</b> , extended, with seats, cu. ft.	-	-	-	-	237.3
<b>Payload<sup>4</sup></b> , lbs.	1955	1644	2736	3599	3279
<b>Gross Vehicle Weight Rating (GVWR)<sup>5</sup></b> , lbs.	7200	7200	8600	9600	9600
<b>Front Gross Axle Weight Rating (GAWR)</b> , lbs.	3600	3600	4100	4300	4300
<b>Rear Gross Axle Weight Rating (GAWR)</b> , lbs.	4000	4000	5360	6084	6084
<b>Fuel capacity</b> , approximate, gallon	31	31	31	31	31
<b>Seating capacity</b> (front/2nd/3rd/4th/5th)	2/3/3/-/-	2/3/3/-/-	2/3/3/4/-	2/3/3/4/-	2/3/3/3/4

<sup>1</sup> Always use safety belts and proper child restraints, even with air bags. Children are safer when properly secured in a rear seat. See the Owner's Manual for more safety information.

<sup>2</sup> Maintenance needs vary with different uses and driving conditions. See owner's manual for details.

<sup>3</sup> OnStar Combines GPS satellite and analog wireless technology, with personal assistance from OnStar Advisors – offering unparalleled safety, security and convenience services. Call 1-800-ONSTAR-7 or visit www.onstar.com for system information and details.

<sup>4</sup> Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo. Cargo and load capacity limited by weight and distribution.

<sup>5</sup> When properly equipped; includes weight of vehicle, passengers, cargo, and equipment.



**Fleet and Commercial**  
Because there's no other business like yours.™