

2004



# Express Cargo

## New For 2004

- Front passenger assist handle standard
- Available Express Access now includes Keyless Entry

## Models

G1500 Regular Wheelbase RWD	(CG13405)
G1500 Regular Wheelbase AWD	(CH13405)
G2500 Regular Wheelbase RWD	(CG23405)
G2500 Regular Wheelbase AWD	(CH23405)
G2500 Extended Wheelbase RWD	(CG23705)
G3500 Regular Wheelbase RWD	(CG33405)
G3500 Extended Wheelbase RWD	(CG33705)

## Powertrain

### Engine

#### Standard

Vortec 4300 V6 MFI

HP (hp @ rpm)	200 @ 4400
Torque (lb-ft @ rpm)	250 @ 2800

#### Available

Vortec 4800 V8 SFI (2500)

HP (hp @ rpm)	270 @ 5200
Torque (lb-ft @ rpm)	285 @ 4000

Vortec 5300 V8 SFI (1500 and 2500)

HP (hp @ rpm)	285 @ 5200
Torque (lb-ft @ rpm)	325 @ 4000

Vortec 6000 V8 SFI (Available 2500; Standard 3500)

HP (hp @ rpm)	300 @ 4400
Torque (lb-ft @ rpm)	360 @ 4000

### Transmission

#### Standard

4-speed automatic, electronically controlled with overdrive, tow/haul mode and internal transmission oil cooler

#### Available

4-speed automatic, heavy-duty, electronically controlled with overdrive, tow/haul mode and external transmission oil cooler

## Fuel Economy [Est. EPA<sup>1</sup> MPG (city/hwy)]

4.3L V6 2WD <sup>1</sup>	15/20
4.8L V8	N/A
5.3L V8 2WD <sup>1</sup>	14/18
AWD	14/18
6.0L V8	N/A

<sup>1</sup> 2003 Information

<sup>2</sup> Based on GM testing. Official EPA estimates not yet available.



Model shown may be equipped with available equipment from independent supplier.

## Select Mechanical Features

S = Standard, A = Available


<b>Alternative fuel conversion-ready engine</b> , includes internal modifications for operation with natural or propane gas	A
<b>Alternator</b> , 105 amps	S
<b>Alternator</b> , 145 amps	A
<b>Battery</b> , 600 cold-cranking amps, includes rundown protection and retained accessory power	S
<b>Battery</b> , heavy-duty, 800 cold-cranking amps, includes rundown protection and retained accessory power	A
<b>Brake/transmission shift interlock</b> , automatic transmission	S
<b>Brakes</b> , 4-wheel antilock, 4-wheel disc	S
<b>Differential</b> , locking, heavy-duty, rear	A
<b>Exhaust</b> , aluminized stainless-steel muffler and tailpipe	S
<b>Frame</b> , ladder-type	S
<b>Oil life monitor</b>	S
<b>Steering</b> , power	S
<b>Suspension</b> , front, independent coil springs, and stabilizer bar (Requires RWD Models)	S
<b>Suspension</b> , front, independent torsion bar (computer selected) and stabilizer bar (Requires AWD Models)	S
<b>Suspension</b> , rear, hypoid drive axle, with multi-leaf springs	S
<b>Trailer wiring</b> , 7-lead harness	A
<b>Trailer equipment<sup>2</sup></b> , heavy-duty, includes trailering hitch platform and 7-lead wiring harness	A

## Select Exterior Features


<b>Bumper</b> , front, painted Black	S
<b>Bumper</b> , rear, painted Black step, includes pad	S
<b>Door</b> , swing-out passenger side, 60/40 split	S
<b>Door</b> , swing-out driver side, 60/40 split	A
<b>Door</b> , sliding passenger side	A
<b>Door</b> beams, steel-side	S
<b>Glass</b> , Solar-Ray light tinted, all windows	S
<b>Glass</b> , Solar-Ray deep tinted (all windows except light tinted glass on windshield, driver and front passenger)	A
<b>Glass</b> , rear doors, fixed	A
<b>Glass</b> , rear doors and side cargo doors, fixed	A
<b>Glass</b> , rear doors, side cargo door, and rear passenger side quarter, fixed	A
<b>Glass</b> , full body window package, fixed	A
<b>Glass</b> , rear door window, swing-out	A
<b>Glass</b> , rear side door and rear door window, swing-out	A
<b>Headlamps</b> , single rectangular halogen	S
<b>Mirrors</b> , outside rearview, manual folding, Black	S
<b>Mirrors</b> , outside rearview, manual folding, power adjust, heated, Black	A
<b>Mirrors</b> , outside rearview, manual folding, power adjust, heated, Black, includes turn signal indicators	A
<b>Tire</b> , spare delete	A
<b>Tires</b> , front and rear, P235/75R16, all-season, blackwall (Available on 1500 Models only)	S
<b>Tire</b> , spare P235/75R16, all-season, blackwall, located at rear underbody of vehicle (Available on 1500 Models only)	S
<b>Tires</b> , front and rear, LT225/75R16E, all-season, blackwall (Requires 8600 lbs. GVWR and available on 2500 Model only)	A
<b>Tire</b> , spare LT225/75R16E, all-season, blackwall, located at rear underbody of vehicle (Requires 8600 lbs. GVWR and available on 2500 Model only)	A
<b>Tires</b> , front and rear, LT245/75R16E, all-season, blackwall (Standard and available on 2500 and 3500 Models only)	S
<b>Tire</b> , spare LT245/75R16E, all-season, blackwall, located at rear underbody of vehicle (Standard and available on 2500 and 3500 Models only)	S
<b>Trim</b> , rear body-colored halo (replaces standard black panels located above rear tail lamps)	A
<b>Wheels</b> , Gray painted, includes Gray center caps and steel spare	S
<b>Wheels</b> , Gray painted, includes chrome center caps and steel spare	A
<b>Wipers</b> , intermittent, front wet-arm with pulse washers	S

## Available Exterior Colors\*

Berry Red Metallic




Black



Dark Gray Metallic



Dark Green Metallic



Indigo Blue Metallic




Light Pewter Metallic



Sandalwood Metallic



Summit White



Victory Red



**Fleet and Commercial**

Because there's no other business like yours.™

www.gmfleet.com • 1-800-FLEETOPS

<sup>2</sup> Maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. See your Chevrolet dealer for additional details.

Information not to be reproduced for any use without permission of GM Fleet and Commercial. Please refer to the GM Online Guide for complete and updated ordering information.

\* Colors may not be available on all models. Actual colors may vary.

# Chevrolet Express Cargo

## Dimensions (in.)

	RWB/LWB
Wheelbase	135.0/155.0
Overall length	224.1/244.1
Body width	79.4/79.4
Overall height	81.6/82.0
Head room, front	40.2/40.2
Shoulder room, front	68.8/68.8
Hip room, front	65.5/65.5
Leg room, front	41.3/41.3
Opening height, side door	47.9/47.9
Opening width, sliding side door	44.1/44.1
Opening height, rear door	49.4/49.4
Opening width, rear door, at belt line	57.0/57.0
Step up height, front door	20.1/19.6
Step up height, side door	20.9/20.5
Front bumper to axle	39.7/39.7
Ground to top of rear load floor	27.7/27.3
Load floor length to front seat, at floor	127.8/147.8
Load floor length to engine cover, at floor	153.6/173.6
Inside width, between wheelhousing	52.7/52.7
Cargo area height	51.9/51.9
Ground clearance, front	8.6/8.4
Ground clearance, rear	7.6/8.1
Sign panel area, side	116.5 x 56.7/136.5 x 56.7

*Published dimensions indicated are without optional equipment or accessories. Additional accessories or equipment ordered at the customer's request can result in a minor change in these dimensions.*

## Standard Safety Features

- Adjustable front shoulder belt guides
- Air bag<sup>1</sup>, dual level driver and front passenger
- Antilock brakes, front and rear
- Automatic daytime running lamps
- Battery, maintenance free<sup>2</sup>
- Brake transmission shift interlock
- Child security rear door locks
- Disc brakes, front and rear with audible wear indicator
- Halogen headlamps
- Laser etched VIN plate
- PASSLock theft deterrent
- Remote hood release
- Side window defogger, front
- Tinted glass windshield
- Tires with built-in tread wear indicators



Model shown may be equipped with available equipment from independent supplier.

## Select Interior Features

S = Standard, A = Available

<b>Air bag<sup>1</sup></b> , frontal, driver side only (deletes passenger side)	A
<b>Air bags<sup>1</sup></b> , frontal, driver and right front passenger	S
<b>Air bag deactivation switch</b> , passenger side (8600 GVWR)	S
<b>Air conditioning delete</b>	A
<b>Air conditioning</b> , front manual	S
<b>Air conditioning</b> , rear	A
<b>Assist handle</b> , front passenger	S
<b>Console</b> , deluxe, includes glove box	A
<b>Cupholders</b> , 3, on engine console cover	S
<b>Defogger</b> , rear-window, electric	A
<b>Defogger</b> , side window	S
<b>Door locks</b> , power, includes Lock-out Protection	A
<b>Floor covering</b> , Black rubberized vinyl, front only (deletes rear covering behind front seats)	A
<b>Floor covering</b> , embossed Black rubberized vinyl full length floor covering	S
<b>Headliner</b> , cloth, over driver and passenger	S
<b>Heater</b> , rear, auxiliary	A
<b>Instrumentation</b> , analog, includes speedometer, odometer with s trip odometer, fuel level, voltmeter, engine temperature and oil pressure	S
<b>Keyless entry</b> , remote, includes 2 transmitters and remote panic button	A
<b>Lighting</b> , 2 dome lamps, includes defeat switch and door handle-activated switches	S
<b>Lighting</b> , auxiliary, includes reading and underhood lights	A
<b>Mirror</b> , inside rearview, manual day/night	S
<b>Power outlet</b> , auxiliary, 2 covered, on engine console cover, 12-volt	S
<b>Seat</b> , driver only high-back reclining bucket, adjustable, includes head restraint and vinyl or cloth trim	A
<b>Seats</b> , front vinyl reclining buckets, includes head restraints	S
<b>Seats</b> , driver and passenger high-back reclining buckets, adjustable, includes head restraints and vinyl or cloth trim	A
<b>Seats</b> , front Custom Cloth buckets, includes head restraints and inboard armrests	A
<b>Sound system</b> , ETR AM/FM stereo with CD player, includes seek-and-scan, digital clock, TheftLock and random select	A
<b>Sound system</b> , ETR AM/FM stereo, includes seek-and-scan and digital clock	S
<b>Sound system</b> , radio delete, deletes antenna, wiring cable, and speakers	A
<b>Steering wheel</b> , steel sleeve column, includes theft-deterrent locking feature, Black	S
<b>Theft-deterrent system</b> , PASSLock	S
<b>Tow/haul mode selector</b> , IP mounted	S
<b>Trim panel delete</b> , rear side and rear doors	A
<b>Visors</b> , padded, driver and passenger side with vinyl trim	S

## Capacities (max.)

	1500 (GG13405)	1500 (CH13405)	2500 (GG23405)	2500 (GG23705)	2500 (CH23405)	3500 (GG33405)	3500 (GG33705)
Curb weight, lbs.	4846	5110	—	5179	5344	5414	5613
Curb weight, (with GVWR <sup>3</sup> , 8600 lbs.), lbs.	—	—	5271	5375	—	—	—
Max. cargo volume, regular, with seats, cu. ft.	225.1	225.1	225.1	—	225.1	225.1	—
regular, with seats removed, cu. ft.	267.3	267.3	267.3	—	267.3	267.3	—
extended, with seats, cu. ft.	—	—	—	261.6	—	—	261.6
extended, with seats removed, cu. ft.	—	—	—	316.8	—	—	316.8
Payload <sup>4</sup> , lbs.	2354	2090	—	2121	1956	4186	3987
Payload <sup>4</sup> , (with GVWR <sup>3</sup> , 8600 lbs.), lbs.	—	—	3329	3225	—	—	—
Gross Vehicle Weight Rating (GVWR) <sup>3</sup> , lbs.	7200	7200	—	7300	7300	9600	9600
Gross Vehicle Weight Rating (GVWR) <sup>3</sup> (with GVWR <sup>3</sup> , 8600 lbs.), lbs.	—	—	8600	8600	—	—	—
Fuel capacity, approximate, gallons	31	31	31	31	31	31	31
Seating capacity	2	2	2	2	2	2	2

<sup>1</sup> Always use safety belts and proper child restraints, even with air bags. Children are safer when properly secured in a rear seat. See the Owner's Manual for more safety information.

<sup>2</sup> Maintenance needs vary with different uses and driving conditions. See owner's manual for details.

<sup>3</sup> When properly equipped; includes weight of vehicle, passengers, cargo, and equipment.

<sup>4</sup> Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo. Cargo and load capacity limited by weight and distribution.



**Fleet and Commercial**  
Because there's no other business like yours.™